

AFRRI TN68-1
FEBRUARY 1968

AFRRI
TECHNICAL
NOTE

NUMIT-ONE AMENDMENT #1

AFRRI TN68-1

ARMED FORCES RADIOBIOLOGY RESEARCH INSTITUTE
Defense Atomic Support Agency
Bethesda, Maryland

Distribution of this document is unlimited.


This report has been approved for open publication by the Department of Defense

NUMIT-ONE AMENDMENT #1

R. W. ROCKWELL



R. E. CARTER
Chairman
Physical Sciences Department



HUGH B. MITCHELL
Colonel, USAF, MC
Director

ARMED FORCES RADIOBIOLOGY RESEARCH INSTITUTE
Defense Atomic Support Agency
Bethesda, Maryland

Distribution of this document is unlimited

TABLE OF CONTENTS

	Page
Foreword (Nontechnical summary)	iii
Abstract	v
I. Introduction	1
II. Accuracy	2
III. Input Limitations	3
IV. Input and Output Formats	3
V. Operation	5
Appendix A	6
Flow Chart A-1	6
Flow Chart A-2	7
Appendix B	8
Appendix C	11
Test Case 1	12
Test Case 2	13
Test Cases 3(a) and 3(b)	14
Appendix D	15
Table I	11

FOREWORD
(Nontechnical summary)

An improvement in NUMIT-ONE (AFRRI Scientific Report SR65-1, October 1965) is described. Simpson's Rule is still used to perform the integration but changes in the coding remove the need for a large array. The number of multiplication operations done during a run has also been vastly reduced resulting in significant savings in machine time.

ABSTRACT

An improvement on NUMIT-ONE, a one-dimensional numerical integration program for the IBM 1620, is reported. Accuracy, input and output formats, source program, flow charts and test problems are discussed.

I. INTRODUCTION

This is an amendment to NUMIT-ONE, a numerical integration program in one-dimension for the IBM 1620 computer, AFRRI Scientific Report SR65-1. Appendix D contains a glossary of terms used in this report.

Further analysis of the problem resulted in the elimination of a large array thereby making the program smaller and the number of multiplication operations fewer. This reduction in size enabled compilation with a larger precision parameter* (thereby increasing accuracy) and the fewer operations decreased the length of running time.

Successive approximations to the integral are now computed with J successively 1, 2, ..., using

$$F_J(a,b) = \frac{\Delta X_J}{3} [f(a) + f(b) + 2 \cdot C_J + 4 \cdot D_J]$$

in which

$$\Delta X_J = \left| \frac{b-a}{2^J} \right|$$

$$C_J = \sum_{m=1}^{2^J-1} f(a + 2m \cdot \Delta X_J), \quad J > 1; \quad C_J = 0 \text{ if } J = 1$$

$$D_J = \sum_{m=1}^{2^J} f(a + [2m-1] \Delta X_J)$$

Thus for the J + 1th iteration:

$$C_{J+1} = D_J + C_J$$

* A precision parameter is the number of arithmetic places to which quantities will be held during computation and may be specified on a control card that precedes the rest of the deck in IBM 1620 FORTRAN II.

and only two summed quantities in the main equation need be multiplied rather than entire arrays.

Input and output formats are slightly changed from the original version.

II. ACCURACY

Reduced truncation error has improved the accuracy. An inherent weakness in Simpson's Rule makes it difficult or impossible to integrate over the intervals of functions where the slope approaches infinity. In the current version it is still difficult but if a large number of iterations are used and the precision parameter is large enough, an accurate answer will be obtained. Test Case 1 (Appendix C) of the current report illustrates this. The slope of this function approaches infinity at the start and end of this interval. By allowing 11 iterations and holding quantities to 10 places, an answer accurate to 5 places was computed.

Breakdown will definitely occur when the integral is close to zero, resulting from an integrand taking on both positive and negative values over the interval of integration. A function such as this should be integrated in parts.

Input for the program has been changed slightly to make this division of the integration interval more amenable and there are no limits on the number of parts used. This situation reveals itself readily by the erratic behavior of DELTA (Δ_J). Test Case 2 (Appendix C) illustrates what happens when integration is attempted over the whole interval of such an integrand and Test Case 3 illustrates the proper method of splitting the integration into parts.

III. INPUT LIMITATIONS

The integrand, $f(x)$, may be any function for which the integral exists; also $(-\infty) < a, b < (+\infty)$, $b \neq a$.

The total number of iterations allowed is J_{\max} (an input parameter) where $2 \leq J_{\max} < 100$. Iteration is stopped whenever either

$$\Delta_J \leq \Delta \quad \text{or} \quad J = J_{\max}$$

While J_{\max} can be any number up to 100, it should not be too high. Each iteration roughly doubles the machine time. Generally, for more than 13 or 14 iterations, machine time is measured in hours.

The integrand, $f(x)$, is provided by a subprogram of the FUNCTION type named FUN(X). FUN must appear on the left of an arithmetic statement whose right is the integrand. The subprogram source deck must be preceded at compilation time by a precision parameter card identical to the precision parameter card, if any was used, of the main source deck.

IV. INPUT AND OUTPUT FORMATS

Input Card Format

The following quantities are specified in the input (floating point numbers are in lower case, fixed point numbers in upper case).

Card 1

Columns 1-80 contain alphanumeric identification. It is reproduced in the output but does not affect the processing.

Card 2

Columns 1-36 Integrand Specification Card. Contains alphanumeric information to identify integrand in output. This does not affect processing.

Card 3

			<u>Format</u>
Columns	1-12	a	E 12.6
Columns	13-24	b	E 12.6
Columns	25-28	Δ	F 4.4
Columns	29-30	J_{\max}	I 2

Following card 3 may be any number of cards specifying new values of a, b, Δ , and J_{\max} . Input format is the same as card 3. The final card is a trailer card with zeros punched in columns 29-30.

Input Deck Assembly

Input decks are assembled as in the original NUMIT-ONE with the FUN(X) subprogram replacing the POINT subprogram.

Errors in Input

The input error check is the same as before except that in the amended version J_{\max} may have any value up to 99. A check is made to see if $J_{\max} < 2$.

Output

The output has three main stages; the identification is punched as follows:

- (a) Alpha Identification Card
- (b) Program name (NUMIT-ONE)
- (c) $F(X)$ = Columns 1-36 of Integrand Specification Card.

Next, the input a , b , J_{\max} , and DELTA 1 are punched followed by the results of the computation with the following data given for each iteration ($J = 2, \dots J_{\text{act}}$):

- (a) Iteration number
- (b) Value of integral
- (c) DELTA

The final value for $\text{DELTA} \leq \text{DELTA } 1$ or $J_{\text{act}} = J_{\max}$ is noted by the term (PASS N) in the last line of the output, where $N = 1, 2, \dots 99$ is the pass number.

If more cards specifying new values of a , b , J_{\max} and DELTA 1 are input, the above cycle will be repeated until all input cards have been processed. The final part of the output is furnished when the trailer card is read. The number of passes (N) is punched, followed by the total value of the integral for all passes. The last card punched, showing satisfactory completion of the program, is "END" and the program stops.


A set of output listings for sample problems is given in Appendix C.

V. OPERATION


Operation is the same as before except a trailer card is now used to stop the computation. No switches are used.

APPENDIX A

Flow Charts



Flow Chart A-1



Flow Chart A-2

APPENDIX B

Source Program

In the program, the following symbols are used which are unexplained in the mathematical description:

N = counter to keep track of number of passes

DELTA 1 = Δ = input convergence criterion

AN1 = F_{J-1} = previous approximation

AN2 = F_J = current approximation

SUMFX = $\sum_{m=1}^{2^{J-1}} f(a + [2m-1] \Delta x)$

SUM = $f(a) + f(b) + \sum_{m=1}^{\frac{2^J}{2}-1} 2 \cdot f(a+2m \cdot \Delta x)$

COUNT = counter used to count successive times $F_J = 0$

*1010

```

C      NUMERIC INTEGRATION USING SIMPSON- ROCKWELL- 2-16-66  AFRII-NNMC
      DIMENSION F(3),P(3),Q(3),U(9)
      P(1)=1.
      P(2)=4.
      P(3)=1.
      Q(1)=1.
      Q(2)=2.
      Q(3)=1.
      N=0
      TOTAL=0.
C
C      READ INPUT AND ALPHA IDENTIFICATION CARD
      READ102
      PUNCH102
      PUNCH103
      READ 114,(U(I),I=1,9)
      PUNCH115,(U(I),I=1,9)
      1 READ101,A,R,DELTA1,JMAX
C
C      TEST INPUT FOR VALIDITY, IF OKAY PUNCH NEXT PART OF OUTPUT
      IF(JMAX-2)26,26,27
      26 IF(N)25,25,29
      25 PUNCH106
      STOP
      27 IF(R-A)22,28,22
      28 PUNCH104
      STOP
      22 IF(DELTA1)23,24,23
      24 PUNCH105
      STOP
      23 PUNCH109,R,JMAX
      PUNCH110,A,DELTA1
C
C      INITIALIZATION FOR START
      CUNIT=0.
      SUM=0.
      SUMFX=0.
      N=N+1
      J=1
      K2=2
      21 DELX=(R-A)/(2.**J)
      IF(J-1)4,2,4
      2 DO 3 I=1,3
      AI=I-1
      X= A+ AI*DELX
      F(I)=FUN(X)
      SUM = SUM+Q(I)*F(I)
      3 SUMFX=SUMFX+P(I)*F(I)
C      FIRST APPROXIMATION OF INTEGRAL
      AN1=DELX*SUMFX/3.
      J=J+1

```

```

      GO TO 21
C     CALCULATES FUNCTION MIDWAY BETWEEN CURRENT PRINTS
4     SUMFX=0.
      DO 5 I=1,K2
      AT = 2*I-1
      X= A+AT*DFLX
5     SUMFX = SUMFX+FUN(X)
C     NEXT APPROXIMATION
      AN2=DFLX*(4.*SUMFX+SUM )/3.
      IF (AN2)6,12,6
6     DELTA=ARCF((AN1-AN2)/AN2*100.)
      IF (DELTA-DELTA1)17,17,18
18    IF (J-JMAX)19,17,17
19    AN1=AN2
      SUM =SUM +2.*SUMFX
      PUNCH112,J,AN1,DELTA
C     INITIALIZATION FOR NEXT ITERATION LOOP
      J=J+1
      K2=2*K2
C     BACK TO ITERATION IF VALUE HAS NOT CONVERGED ENOUGH
      GO TO 21
C
C     PUNCH FINAL ANSWER FOR THIS PASS AND RETURN FOR NEXT INPUT CARD
17    PUNCH 113,J,N,AN2,DELTA
      TOTAL =TOTAL+AN2
      GO TO 1
C
C     FOR HANDLING ZERO ANSWERS
12    COUNT=COUNT+1.
      IF (COUNT-2.)18,17,17
C
C     PUNCH THE TOTAL ANSWER AND HALT
29    PUNCH116,N,TOTAL
      STOP
101   FORMAT(2F12.6,F4.4,I2)
102   FORMAT(80H
1
103   FORMAT(/15X,48HNUMIT ONE (ONE-DIM. INTEGRATION, SIMPSONS RULE) )
104   FORMAT(15X,17HCHECK INPUT - A=R)
105   FORMAT(15X,22HCHECK INPUT - DELTA1=0)
106   FORMAT(15X,32HCHECK INPUT - JMAX OUTSIDE RANGE)
109   FORMAT(35X,10HINPUT DATA/20X,2HA=F12.6,11X,7HJ(MAX)=,I2)
110   FORMAT(20X,2HA=,F12.6,11X,7HDELTA1=,F10.4//15X,10H ITERATION,11X,
18HINTEGRAL,13X,5HDELTA)
112   FORMAT(19X,I2,12X,F12.6,10X,F8.3)
113   FORMAT(19X,I2,5H(PASS,I3,1H),3X,F12.6,10X,F8.3////)
114   FORMAT(9A5)
115   FORMAT(16X,7HF(X) = ,9A5,/)
116   FORMAT(32X,12HNO. PASSES =I3/29X,16HTOTAL INTEGRAL = F12.5/39X,
13HEND)
      END

```

APPENDIX C

Test Cases

Running time is still highly variable, but in general the time is now 30 to 50 per cent faster than in the old version as will be noted in the test cases. Also, accuracy has been increased since quantities are now held to 10 significant figures.

Note the integrands of Cases 3(a) and 3(b) are identical to Case 2 and taken together duplicate Case 2. However, Case 3 produced a more accurate answer in a small fraction of the time for Case 2 because the Case 2 integral took on positive and negative values during the iteration attempting to approximate a zero answer while Case 3 integrated nonzero portions and summed them.

Running time, as in the original report, is still dependent on the formula

$$t = K \cdot 2^{J_{act}}$$

Table I gives the new running times for the test cases.

TABLE I

Test #	Integrand	a	b	J_{act}	t	$\frac{t_{new}}{t_{old}} \times 100$	K (min)
1	$\sqrt{(1-x^2)(2-x)}$	-1	1	11	12'50"	51.5	6.27×10^{-3}
2	$\sin(x)$	0	2π	11	16'50"	64.9	8.22×10^{-3}
3(a)	$\sin(x)$	0	π	5	1'	-	8.22×10^{-3}
3(b)	$\sin(x)$	π	2π	5	1'	-	8.22×10^{-3}

TEST CASE 1

INPUT DATA

SOURCE STATEMENT OF SUBROUTINE

```
*1010
```

```
FUNCTION FUN(X)
FUN = SQRTF((1.-X*X)*(2.-X))
RETURN
END
```

OUTPUT DATA

TEST FUNCTION 1

```
NUMIT ONE %ONE-DIM. INTEGRATION, SIMPSONS RULE
F%X# # SQRT%%1.-X*X#2.-X#
```

INPUT DATA

```
B# .100000E&01      J%MAX#13
A#-.100000F&01      DELTA1# .1000E-02
```

ITERATION	INTEGRAL	DELTA
2	.209138E&01	9.838
3	.216390F&01	3.351
4	.218943F&01	1.166
5	.219843F&01	.409
6	.220161E&01	.144
7	.220273F&01	.050
8	.220312F&01	.017
9	.220326F&01	.006
10	.220331F&01	.002
11%PASS 1#	.220333F&01	0.000

```
NO. PASSES # 1
TOTAL INTEGRAL # 2.20333E-00
END
```

TEST CASE 2

INPUT DATA

SOURCE STATEMENT OF SUBROUTINE

*1010

```
FUNCTION FUN(X)
FUN = SIN(X)
RETURN
END
```

OUTPUT DATA

TEST FUNCTION 2

```
NUMIT ONE %ONE-DIM. INTEGRATION, SIMPSONS RULE
F%X# SIN%X#
```

INPUT DATA

```
B# .628319E+01 J%MAX#11
A# .000000E-99 DELTA1# .1000E-02
```

ITERATION	INTEGRAL	DELTA
3	-.628319E-09	100.000
4	-.523599E-09	20.000
5	.641408E-09	181.632
6	-.615229E-09	204.255
7	-.187841E-08	67.247
8	-.144971E-08	29.571
9	.397608E-09	464.609
10	-.443300E-08	108.969
11%PASS 1#	-.274807E-08	61.312

```
NO. PASSES # 1
TOTAL INTEGRAL #-2.74807E-09
END
```

TEST CASES 3(a) and 3(b)

OUTPUT DATA

TEST FUNCTIONS 3(a) and 3(b)

NUMIT ONE %ONE-DIM. INTEGRATION, SIMPSONS RULE#
F%X# # SIN%X#

INPUT DATA

B# .314159E&01	J%MAX#11
A# .000000E-99	DELTA1# .1000E-02

ITERATION	INTEGRAL	DELTA
2	.200455E&01	4.481
3	.200026E&01	.214
4	.200001E&01	.012
5%PASS 1#	.200000E&01	0.000

INPUT DATA

B# .628319E&01	J%MAX#11
A# .314159E&01	DELTA1# .1000E-02

ITERATION	INTEGRAL	DELTA
2	-.200455E&01	4.481
3	-.200026E&01	.214
4	-.200001E&01	.012
5%PASS 2#	-.200000E&01	0.000

NO. PASSES # 2
TOTAL INTEGRAL # 0.00000E-99
END

APPENDIX D

Glossary

$F_J(a,b)$	-- the approximation of the integral for the Jth iteration over the interval (a,b)
ΔX_J	-- the mesh interval for the Jth iteration
$f(x)$	-- the integrand
C_J	-- the sum of the values of the integrand over the interval (a,b) whose coefficients are 2
D_J	-- the sum of the values of the integrand over the interval (a,b) whose coefficients are 4
J	-- used to denote iteration number
Δ_J	-- convergence number calculated for the Jth iteration
Δ	-- input convergence criterion number
a	-- beginning point of the integration interval
b	-- end point of the integration interval
m	-- used as an index in summation
J_{\max}	-- maximum number of iterations permitted
J_{act}	-- actual number of iterations
K	-- constant used in estimating running time

DISTRIBUTION LIST

AIR FORCE

Office of the Surgeon General, Department of the Air Force, Headquarters U. S. Air Force, Washington, D. C. 20333 (1)

Air Force Institute of Technology, Air University, USAF, Wright-Patterson Air Force Base, Ohio 45433 (1)

ARMY

The Surgeon General, Department of the Army, Washington, D. C. 20315 (1)

Director, Walter Reed Army Institute of Research, Washington, D. C. 20012 (1)

Chief of Research and Development, Department of the Army, Washington, D. C. 20310, ATTN: Nuclear, Chemical and Biological Division (1)

Commanding Officer, U. S. Army Nuclear Defense Laboratory, Edgewood Arsenal, Maryland 21040 (1)

NAVY

Chief, Bureau of Medicine and Surgery, Department of the Navy, Washington, D. C. 20390 (1)

Chief of Naval Research, Department of the Navy, Washington, D. C. 20390 (1)

Director, U. S. Naval Research Laboratory, Washington, D. C. 20390 (1)

Commanding Officer and Director, U. S. Naval Radiological Defense Laboratory, San Francisco, California 94135 (1)

Chief of Naval Operations, Department of the Navy, Washington, D. C. 20350, ATTN: Director, Atomic Energy Division (1)

Commanding Officer, U. S. Naval Hospital, NNM, Bethesda, Maryland 20014, ATTN: Director, REEL (1)

D. O. D.

Director, Defense Atomic Support Agency, Washington, D. C. 20305 (1)

Director, Defense Atomic Support Agency, Washington, D. C. 20305, ATTN: DDST (1)

Director, Defense Atomic Support Agency, Washington, D. C. 20305, ATTN: Chief, Radiation Directorate (1)

Director, Defense Atomic Support Agency, Washington, D. C. 20305, ATTN: Medical Directorate (4)

Director, Defense Atomic Support Agency, Washington, D. C. 20305, ATTN: Technical Library (2)

Commander, Field Command, Defense Atomic Support Agency, Sandia Base, Albuquerque, New Mexico 87115 (1)

Defense Documentation Center, Cameron Station, Alexandria, Virginia 22314 (20)

OTHER GOVERNMENT

U. S. Atomic Energy Commission, Washington, D. C. 20545 (1)

U. S. Atomic Energy Commission, Division of Peaceful Nuclear Explosives, Washington, D. C. 20545 (1)

National Library of Medicine, Bethesda, Maryland 20014 (1)

OTHER

Scientific Committee on the Effects of Atomic Radiation, United Nations, Room 3267, New York, N. Y. 10017 (1)

Argonne National Laboratory, 9700 South Cass Avenue, Argonne, Illinois 60440 (1)

Los Alamos Scientific Laboratory, Los Alamos, New Mexico 87544 (1)

Oak Ridge Institute of Nuclear Studies, Oak Ridge, Tennessee 37831 (1)

Lawrence Radiation Laboratory, University of California, Livermore, California 94551 (1)

Brookhaven National Laboratory, Upton, Long Island, New York 11973 (1)

Director of Research, Lovelace Foundation, 4800 Gibson Boulevard, Albuquerque, New Mexico 87108 (1)

1620 Users Group Newsletter, Computer Center, Georgia State College, 33 Gilmer Street, Atlanta, Georgia 30303

ATTN: Professor W. H. Wells (1)

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Armed Forces Radiobiology Research Institute Defense Atomic Support Agency Bethesda, Maryland 20014		2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2b. GROUP N/A	
3. REPORT TITLE NUMIT-ONE AMENDMENT #1			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			
5. AUTHOR(S) (Last name, first name, initial) Rockwell, R. W.			
6. REPORT DATE February 1968		7a. TOTAL NO. OF PAGES 19	7b. NO. OF REFS 0
8a. CONTRACT OR GRANT NO.		9a. ORIGINATOR'S REPORT NUMBER(S) AFRRI TN68-1	
b. PROJECT NO.			
c. R MD 4 908		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.			
10. AVAILABILITY/LIMITATION NOTICES Distribution of this document is unlimited			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY Defense Atomic Support Agency Washington, D. C. 20305	
13. ABSTRACT An improvement on NUMIT-ONE, a one-dimensional numerical integration program for the IBM 1620, is reported. Accuracy, input and output formats, source program, flow charts and test problems are discussed.			

UNCLASSIFIED
Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.